



Product Service

# CERTIFICATE

No. Z1A 17 11 94747 010

**Holder of Certificate:** **Xinsu Global Electronic Co., Limited**  
 Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road  
 Central  
 HONG KONG

**Certification Mark:**



**Product:** **Switching power supply unit  
 (SWITCHING POWER SUPPLY/CHARGER)**

**Tested according to:** EN 62368-1:2014  
 AfPS GS 2014:01 PAK 3.1

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

**Test report no.:** 652101711301

**Valid until:** 2022-11-28

**Date,** 2017-12-07 (Ricky Wang)





Product Service

**CERTIFICATE**  
**No. Z1A 17 11 94747 010**

**Model(s):** XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM,  
 XSGxxxxxy, XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz,  
 XSECxxxxxy, XSECxxxxxyzz  
 (xxx=042-730, which denotes the rated output voltage  
 from 4.2VDC to 73.0VDC; yyyy=0300-9999, which denotes  
 the rated output current from 300mA to 9999mA; zz=EU or  
 UK, which denotes for marketing purpose and not affect  
 safety, EU=Europe, UK=United Kingdom.)  
 XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM,  
 XSGxxxxxy, XSGxxxxxyzz, XSExxxxxy,  
 XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz  
 (xxx=042-190, which denotes the rated output voltage from  
 4.2VDC to 19.0VDC; yyyy=10000-11000, which denotes  
 the rated output current from 10000mA to 11000mA;  
 zz=EU or UK, which denotes for marketing purpose and  
 not affect safety, EU=Europe, UK=United Kingdom.)

**Parameters:**

Rated Input :	100-240VAC, 50/60Hz, 3.0A Max.
Rated Output :	See page 3 for details
Protection Class :	I (For models XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM, XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM); II (For models XSGxxxxxy, XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz, XSGxxxxxy, XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz)
Degree of Protection :	IP20

**Factory(ies):** 94748

**CERTIFICATE**  
**No. Z1A 17 11 94747 010**



Product Service

Model No.	Rated output voltage (VDC)	Rated output current (mA)	Max. rated output power (W)
XSGxxxxxyyyyMM,	4.2-9.0	10000	90.0
XSExxxxxyyyyMM,	9.1-14.6	10000-11000	160.6
XSECxxxxxyyyyMM,	14.7-17.0	10000	170.0
XSGxxxxxyyyy,	17.1-19.0	10000	190.0
XSGxxxxxyyyyzz,			
XSExxxxxyyyy,			
XSExxxxxyyyyzz,			
XSECxxxxxyyyy,			
XSECxxxxxyyyyzz			
XSGxxxxxyyyyMM,	4.2-9.0	300-9999	90.0
XSExxxxxyyyyMM,	9.1-14.6	300-9999	146.0
XSECxxxxxyyyyMM,	14.7-17.0	300-9999	170.0
XSGxxxxxyyyy,	17.1-19.0	300-9999	190.0
XSGxxxxxyyyyzz,	19.1-22.0	300-9500	190.0
XSExxxxxyyyy,	22.1-32.0	300-8500	205.8
XSExxxxxyyyyzz,	32.1-36.5	300-6000	219.0
XSECxxxxxyyyy,	36.6-57.9	300-5000	210.0
XSECxxxxxyyyyzz	58.0-58.8	300-3600	210.2
	58.9-73.0	300-3400	204.0